

# GLC SERIES

GRADE 3



## FEATURES:

- Door Thickness: 1 3/8" - 1 7/8" range
- Backset: 2 3/4"
- Cylinder: Schlage Solid Brass "C" keyway
- Keying: Schlage 5 pin keyed
- Key: 2 five pin Nickel Plated
- Functions: See below
- Construction: Steel, Zinc Dichromated resists corrosion
- Heavy duty spring cage reinforced for lever return
- Latch: 1/2" projection Stainless Steel
- Face: 1 1/8" x 2 1/4"
- Bore: 2 1/8" hole retrofits grade 3 cylindrical locksets
- Fits 161 Prep doors
- Strike: ANSI 1 1/4" x 4 7/8" strike
- Warranty: 1 year mechanical and finish
- Finish: US26D

## OPTIONS:

- 2 3/8" backset, Deadlatch
- 2 3/8" backset, Springlatch
- DL-EXBS5: Extension for 5" backset

## KEYING OPTIONS:


(additional charges may apply)

- 2 keys per cylinder
- KD: Keyed Different
- KA: Keyed Alike
- KA2: Keyed Alike; groups of 2
- KEYWAYS: SC5

## CROSS REFERENCE

FUNCTION	TA	HAGAR	CAL-ROYAL	PDQ	TELL
PASSAGE	GLC-5110	3610	803	SF126	LT3575
PRIVACY	GLC-5140	3640	802	SF176	LT3576
ENTRY	GLC-5151	3653	800	SF116	LT3581
STOREROOM	GLC-5180	3680		SF115	

## DOOR PREP DIAGRAM



www.impusa.com

## LIGHT DUTY COMMERCIAL CYLINDRICAL LEVEL & KNOB

The GLC Series cylindrical locksets are designed for use on all light duty Grade 3 commercial and residential applications. The GLC commercial lever is ADA compliant.



GLC KNOB



### CODE COMPLIANCE

- ANSI A117.1 ADA Barrier-free Accessibility